



## PRODUCT SPECIFICATIONS

### sSORB® AB1530G

Silica Gel, Type A, Blue Indicating, 1.5 - 3.0 mm, Granular

**CHEMICAL FORMULA**  $\text{SiO}_2 \cdot n\text{H}_2\text{O} + \text{CoCl}_2$

#### PRODUCT DESCRIPTION

sSORB® AB1530G silica gel is the naturally occurring mineral silicon dioxide that has been purified and processed into a hard, smooth beaded form. The beads are then saturated with a moisture indicating solution that gives them a deep blue color when dry. It is also known as a narrow pore silica gel and has a vast network of interconnecting pores with diameters of 20-30Å. These pores have a strong affinity for moisture and use physical adsorption and capillary condensation to trap and hold it. Silica gel will remove moisture at temperatures as high as 220°F, but is best used at room temperature (70-90°F) and high relative humidity (60-90%Rh). The color changes from blue to purple to pink as it adsorbs moisture.

SPECIFICATIONS		
Property	Value	Unit
Granular Size	1.5 - 3.0	mm
Nominal Pore Opening	20 - 30	Angstroms
Color Change	Blue to Pink	Indication
pH(Slurry)	≈ 7	pH
Water Adsorption Capacity		
20%	≥ 11	% Weight
40%	≥ 22	% Weight
80%	≥ 33	% Weight
Bulk Density	≥ 780	g/l
	≥ 48	lbs/ft <sup>3</sup>
Size Qualification	≥ 97	%
Package Moisture	≤ 1.5	% Weight

#### TYPICAL APPLICATIONS

As a primary desiccant or blended with other desiccants in any application where visual control of moisture is required, such as compressed air dryers, gas drying, breathers, for protection of non consumable packaged goods, drying and storage of flowers and seeds, etc. Due to the addition of the moisture indicator, sSORB® AB1530G Indicating Silica Gel should not be used in contact with products intended for consumption such as food or pharmaceuticals.

#### PACKAGING INFORMATION

Bags                25 kgs  
Drums             Fill weights to order specification  
Super Sacks      Fill weights to order specification

#### HANDLING & STORAGE RECOMMENDATIONS

Store sSORB® silica gel in a dry location to prevent premature water adsorption. Reseal packages after opening to prevent contamination and unintended water adsorption. We recommend that you rotate stock so oldest material is used first.

#### HEALTH & SAFETY INFORMATION

Health and Safety Information is available on product MSDS, which can be downloaded from our web site [www.deltaadsorbents.com](http://www.deltaadsorbents.com) or by contacting Delta Adsorbents at 800.274.3205.

#### DISTRIBUTED BY:

**Delta Adsorbents**  
24 Congress Circle  
Roselle, IL 60172

**Phone:** 800.274.3205  
**Fax:** 630.980.5286



Product