



630.980.5205

R-Series – High Vibration Applications

Model	Height inches (cm)	Diameter inches (cm)	Mounting Connection	Silica Gel lbs (kg)	Maximum Adsorption Capacity fl. ounces (mL)	Maximum Air Flow cfm	Maximum Reservoir Fluid Flow gpm	Type of Medium	Uses Replacement Cartridge	Use With
R-100	5 (12.7)	5.2 (13.2)	1" MNPT	0.8 (0.4)	4.91 (145)	25	187	100% Silica Gel	A-300	
R-101	6.5 (16.5)	5.2 (13.2)	1" MNPT	1.4 (0.6)	8.6 (254)	25	187	100% Silica Gel	A-301	
R-102	9.5 (24.1)	5.2 (13.2)	1" MNPT	2.7 (1.2)	16.56 (489)	25	187	100% Silica Gel	A-302	
R-111	6 (15.2)	5.2 (13.2)	1.125" Female thread	1.4 (0.6)	8.6 (254)	25	187	100% Silica Gel	A-301	A-306
R-121	6.5 (16.5)	5.2 (13.2)	2" MNPT	1.4 (0.6)	8.6 (254)	25	187	100% Silica Gel	A-321	
R-122	9.5 (24.1)	5.2 (13.2)	2" MNPT	2.7 (1.2)	16.56 (489)	25	187	100% Silica Gel	A-322	
R-123	12 (30.5)	5.2 (13.2)	2" MNPT	3.5 (1.6)	21.47 (634)	25	187	100% Silica Gel	A-323	