

<b>SECTION 1: PRODUCT AND COMPANY IDENTIFICATION</b>		
PRODUCT IDENTIFIER	CelaClear™ 105SF	
CHEMICAL NAME	Bentonite, Acid Leached	
CHEMICAL FAMILY	Clay	
MATERIAL USE	Bleaching Clay	
RESTRICTION ON USE	None Known	
MANUFACTURER	EP Engineered Clays Corporation, 600 East McDowell Road Jackson, MS 39204	
TELEPHONE NO.	(601) 985-4857 (Monday – Friday 8:00 am PST – 5:00 pm PST)	
EMERGENCY TELEPHONE NO.	(601) 985-4857 (Monday – Friday 8:00 am PST – 5:00 pm PST)	
SDS DATE OF PREPARATION	July 16, 2018	
<b>SECTION 2: HAZARDS IDENTIFICATION</b>		
OSHA GHS HAZARD CLASSIFICATION	Carcinogen Category 1A Specific Target Organ Toxicity, Repeated Exposure Category 1	
HAZARDS NOT OTHERWISE CLASSIFIED	None	
LABEL ELEMENTS	<p><b>DANGER</b>            May cause cancer by inhalation.            Causes damage to lungs through prolonged or repeated exposure.            Obtain special instructions before use.            Do not handle until all safety precautions have been read and understood.            Do not breathe dust.            Wear eye protection.            If exposed or concerned: Get medical advice.            Dispose of contents in accordance with local, state and federal regulations.</p> 	
<b>SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS</b>		
INGREDIENT IDENTIFICATION	APPROXIMATE CONCENTRATION (%)	C.A.S. NUMBERS
Bentonite, Acid Leached (contains 1-5% Crystalline Silica - Quartz)	100%	70131-50-9 14808-60-7
<b>SECTION 4: FIRST AID MEASURES</b>		
EYE	Flush eyes with generous quantities of water or eye rinse solution. Consult physician if irritation persists.	
SKIN	Use moisture renewing lotions if dryness occurs.	
INGESTION	Drink generous amounts of water to reduce bulk and drying effects.	
INHALATION	Remove to fresh air. Blow nose to evacuate dust.	
Most important symptoms/effects, acute and delayed	Dust may cause abrasive irritation to eyes. Prolonged skin contact may cause dryness. Dust may cause nose, throat and upper respiratory tract irritation. Prolonged inhalation of respirable dust containing silica may cause a progressive lung disease, silicosis and lung cancer. See Section 11 for additional information.	
Indication of immediate medical attention and special treatment, if necessary	Immediate medical attention is not normally required. If dust irritates the eyes, seek medical attention.	

MATERIAL NAME	CelaClear™ 105SF	Page 2 of 4
---------------	------------------	-------------

## SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA	Not applicable, the material is not combustible.
SPECIFIC HAZARDS ARISING FROM THE CHEMICAL	Not applicable, the material is not combustible.
SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS	Not applicable, the material is not combustible.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS	If dust is present, use respirator fitted with particulate filter as specified in Section 8. Protect eyes with goggles. Do not breathe dust.
ENVIRONMENTAL PRECAUTIONS	This material is not a significant environmental concern.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	Vacuum clean spillage or wet sweep. Caution: wet product will be slippery. Avoid creating airborne dust. Place in a container for use or disposal.

## SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	Minimize dust generation. Avoid contact with eyes. Do not breathe dust. Use only with adequate ventilation and dust collection. Repair or dispose of broken bags. Follow good housekeeping procedures to minimize the accumulation of dust in the work area. Remove contaminated clothing and wash it before reuse. Product forms slippery surfaces when wet – use caution. Observe all label precautions and warnings.
CONDITIONS FOR SAFE STORAGE	Store in a dry place to maintain packaging integrity and product quality. Store product separately from feed, food, pesticides and fertilizers so that cross contaminations does not occur. Do not store near hydrofluoric acid or concentrated caustic solutions.

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES:	Note: Processing of sorptive clays is not covered by the OSHA Silica Standard (29CFR1910.1053) and the OSHA PEL associated with that standard.			
Component	OSHA PEL	ACGIH TLV	MSHA PEL	NIOSH REL
Bentonite, Acid Leached (as Particulates not otherwise classified)	5 mg/m <sup>3</sup> respirable dust 15 mg/m <sup>3</sup> total dust	None Established	5 mg/m <sup>3</sup> respirable dust 15 mg/m <sup>3</sup> total dust	None Established
Crystalline Silica (Quartz)	30 mg/m <sup>3</sup> % SiO <sub>2</sub> +2 total dust  10 mg/m <sup>3</sup> % SiO <sub>2</sub> +2 Respirable dust	0.025 mg/ m <sup>3</sup> Respirable dust	30 mg/m <sup>3</sup> % SiO <sub>2</sub> +2 total dust  10 mg/m <sup>3</sup> % SiO <sub>2</sub> +2 Respirable dust	0.05 mg/ m <sup>3</sup> Respirable dust
ENGINEERING CONTROLS	Use general or local exhaust ventilation to control dust within recommended exposure limits. Refer to ACGIH publication "Industrial Ventilation" or similar publications for design of ventilation systems.			
PERSONAL PROTECTIVE EQUIPMENT:				
EYE / FACE PROTECTION	Goggles to protect from dust			
SKIN PROTECTION	No special equipment is needed.			
RESPIRATORY PROTECTION	If the exposure limits are exceeded, a NIOSH approved respirator appropriate for the form and concentration of the contaminants should be used. For example, if the dust concentration is less than ten (10) times the Permissible Exposure Limit (PEL), use a quarter or half-mask respirator with an N95 dust filter or a single-use dust mask rated N95. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134; or in Canada with CSA Standard Z94.4 and good industrial hygiene practice.			
GENERAL HYGIENE	Avoid breathing dust. Avoid contact with eyes. Wash hands after handling and before eating or drinking.			

<b>MATERIAL NAME</b>	CelaClear™ 105SF	Page 3 of 4
----------------------	------------------	-------------

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>APPEARANCE, COLOR</b>	Off-white to light grey powder	<b>ODOR</b>	Odorless
<b>PHYSICAL STATE</b>	Solid	<b>ODOR THRESHOLD</b>	Not applicable
<b>VAPOR PRESSURE</b>	Not applicable	<b>VAPOR DENSITY</b>	Not applicable
<b>BOILING POINT</b>	Not applicable	<b>MELTING POINT</b>	>450 °C
<b>FLASH POINT</b>	Not applicable	<b>pH (10% SUSPENSION)</b>	Unknown
<b>FLAMMABILITY LIMITS</b>	Not applicable	<b>EVAPORATION RATE</b>	Not applicable
<b>DECOMPOSITION TEMPERATURE</b>	Unknown	<b>SPEC. GRAVITY / RELATIVE DENSITY</b>	2.28 g/cm <sup>3</sup>
<b>AUTOIGNITION TEMPERATURE</b>	Not applicable	<b>PARTITION COEFFICIENT – n-OCTANOL/WATER</b>	Not applicable
<b>FLAMMABILITY (solid/gas)</b>	Not applicable	<b>SOLUBILITY – WATER</b>	< 1 mg/l
		<b>VISCOSITY</b>	Not applicable

## SECTION 10: STABILITY AND REACTIVITY

<b>REACTIVITY</b>	Material is not reactive.
<b>CHEMICAL STABILITY</b>	Material is stable.
<b>POSSIBILITY OF HAZARDOUS REACTIONS</b>	Material is not reactive under normal conditions of handling unless mixed with incompatible substances below.
<b>CONDITIONS TO AVOID</b>	Not applicable
<b>INCOMPATIBLE MATERIALS</b>	Unsaturated organic compounds, such as turpentine and vegetable oil. Hydrofluoric acid and concentrated caustic solutions may react with the product. Strong oxidizing agents.
<b>HAZARDOUS DECOMPOSITION PRODUCTS</b>	Not applicable

## SECTION 11: TOXICOLOGICAL INFORMATION

<b>POTENTIAL HEALTH EFFECTS</b>	
<b>Likely Routes of Exposure</b>	See below
<b>EYE</b>	May cause irritation (tear formation and redness) if dust gets in eyes.
<b>SKIN</b>	Not absorbed by the skin, but may cause dryness if prolonged exposure.
<b>INGESTION</b>	Ingestion of small quantities is not considered harmful, but may cause irritation of the mouth, throat and stomach.
<b>INHALATION</b>	Acute inhalation can cause dryness of the nasal passage and lung congestion, coughing and general throat irritation. Acute inhalation of high concentrations of respirable crystalline silica may cause acute silicosis.
<b>CHRONIC EFFECTS</b>	This product contains naturally occurring crystalline silica. Respirable crystalline silica may cause lung cancer and lung disease (silicosis) if inhaled for prolonged periods. Symptoms of silicosis include wheezing, cough and shortness of breath.
<b>CARCINOGENICITY</b>	This product is composed predominantly of clay, but contains some crystalline silica. Respirable crystalline silica (quartz) is classified by OSHA, IARC and NTP as a known human carcinogen. Crystalline silica is only known to cause cancer when inhaled in a respirable form. It is not known to cause cancer by any other route of exposure.
<b>NTP</b>	Respirable crystalline silica (quartz) is classified as a known human carcinogen.
<b>IARC</b>	Respirable crystalline silica (quartz) is classified as a known human carcinogen.
<b>NUMERICAL MEASURES OF TOXICITY</b>	Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

MATERIAL NAME	CelaClear™ 105SF	Page 4 of 4
CORROSIVENESS, SENSITIZATION, IRRITANCY	Not irritating	
REPRODUCTIVE TOXICITY	Not adverse effects on reproduction are known.	
TERATOGENICITY, MUTAGENICITY	No adverse effects on development are known.	
<b>SECTION 12: ECOLOGICAL INFORMATION</b>		
ECOTOXICITY:	No toxicity is expected	
PERSISTENCE AND DEGRADABILITY	Non-biodegradable, inert.	
BIOACCUMULATIVE POTENTIAL	Little potential for bioaccumulation	
MOBILITY IN SOIL	No mobility	
OTHER ADVERSE EFFECTS	None known	
<b>SECTION 13: DISPOSAL CONSIDERATIONS</b>		
WASTE DISPOSAL	If this material as supplied becomes a waste, use solid waste disposal common to landfill type operations or in slurry to sumps. Not considered a hazardous waste under RCRA (40CFR Part 261).	
PACKAGING DISPOSAL	Dispose of in accordance with applicable laws and regulations, typically solid waste disposal common to landfill type operations.	
<b>SECTION 14: TRANSPORT INFORMATION</b>		
BASIC SHIPPING INFORMATION	Not regulated as a hazardous material for transport.	
ADDITIONAL INFORMATION	No special requirements or placarding necessary.	
<b>SECTION 15: REGULATORY INFORMATION</b>		
U.S. FEDERAL:		
TSCA	Bentonite, Acid Leached and Quartz appear on the EPA TSCA inventory list.	
CERCLA	Bentonite is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR 302.	
SARA TITLE III	Not listed.	
California Proposition 65:	⚠️ <b>WARNING:</b> This product can expose you to crystalline silica, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .	
<b>SECTION 16: OTHER INFORMATION</b>		
	<p>NFPA</p> <p>4-Extreme 3-High 2-Moderate 1-Slight</p>	<p>HMIS</p> <p>0* Health</p> <p>0 Flammability</p> <p>0 Reactivity</p> <p>E Protective Equipment</p>
ORIGINAL ISSUE DATE	July 16, 2018	
REVISION DATE	July 16, 2018	
REVISION NO.	1	

**Disclaimer:** As of the date of the preparation of this document, the foregoing information is believed to be accurate and is provided in good faith to comply with applicable federal and state laws. No warranty, representation or guaranty of any kind, express or implied, is hereby provided or intended with respect to the completeness of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by the purchase, resale, use or exposure to our product. Customer users of silica must comply with all applicable health and safety laws, regulations and orders, including OSHA Hazardous Communication Standard.